



SAFETY DATA SHEET

1. Identification

Product identifier	Perfect 10 Aerosol	
Other means of identification		
Product Code	114520	
Recommended use	Not available.	
Recommended restrictions	None known.	
Manufacturer/Importer/Supplier/Distributor information		
Manufacturer		
Company name	Malco Products, Inc.	
Address	361 Fairview Ave Barberton, OH 44203 United States	
Telephone	Phone	800-253-2526
	Fax	330-753-2025
Website	www.malcopro.com	
E-mail	msdsinfo@malcopro.com	
Contact person	Technical Department	
Emergency phone number	Phone	1-800-424-9300
Supplier	Not available.	

2. Hazard identification

Physical hazards	Aerosols	Category 1
Health hazards	Skin corrosion/irritation	Category 2
	Sensitization, skin	Category 1
	Reproductive toxicity	Category 2
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Specific target organ toxicity, repeated exposure	Category 2
Environmental hazards	Not classified.	

Label elements



Signal word	Danger
Hazard statement	Extremely flammable aerosol. Pressurized container: May burst if heated. May be fatal if swallowed and enters airways. Causes skin irritation. May cause an allergic skin reaction. May cause respiratory irritation. May cause drowsiness or dizziness. Suspected of damaging fertility or the unborn child. Suspected of damaging fertility. May cause damage to organs through prolonged or repeated exposure.
Precautionary statement	
Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

Response	IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. IF ON SKIN: Wash with plenty of water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF exposed or concerned: Get medical advice/attention. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.
Storage	Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Supplemental information	57% of the mixture consists of component(s) of unknown acute inhalation toxicity.
Other hazards	None known.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
butane		106-97-8	40 - < 50
hexane		110-54-3	20 - < 30
Naphtha (Petroleum), Hydrotreated Light		64742-49-0	10 - < 20
cyclohexane		110-82-7	< 1
heptane		142-82-5	< 1
Other components below reportable levels			20 - < 30

DSD: Directive 67/548/EEC.

CLP: Regulation No. 1272/2008.

M: M-factor

vPvB: very persistent and very bioaccumulative substance.

PBT: persistent, bioaccumulative and toxic substance.

#: This substance has been assigned Community workplace exposure limit(s).

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments The full text for all H-statements is displayed in section 16. The full text for all R- and H-phrases is displayed in section 16.

4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician or poison control center immediately.

Skin contact

Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions.

Eye contact

Rinse with water. Get medical attention if irritation develops and persists.

Ingestion

In the unlikely event of swallowing contact a physician or poison control center.

Most important symptoms/effects, acute and delayed

Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness or dizziness. Nausea, vomiting. May cause respiratory irritation. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash. Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information

Immediate medical attention is required. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Foam. Powder. Carbon dioxide (CO2).

Unsuitable extinguishing media

Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Firefighters should wear full protective clothing including self contained breathing apparatus. Structural firefighters protective clothing will only provide limited protection.

Fire fighting equipment/instructions

In case of fire and/or explosion do not breathe fumes. Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Self-contained breathing apparatus and full protective clothing must be worn in case of fire. In the event of fire and/or explosion do not breathe fumes.

General fire hazards

Extremely flammable aerosol.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Consider initial downwind evacuation for at least 500 meters (1/3 mile). Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Do not breathe gas. Fully encapsulating, vapor protective clothing should be worn for spills and leaks with no fire. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Vapors may form explosive mixtures with air. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not breathe mist or vapor. Do not breathe gas. Do not get this material in contact with eyes. Do not get this material in contact with skin. Do not get this material on clothing. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using do not eat or drink. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only in area provided with appropriate exhaust ventilation. Wear appropriate personal protective equipment. Wash thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Keep locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. The pressure in sealed containers can increase under the influence of heat. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in tightly closed container. Store in a well-ventilated place. Keep away from food, drink and animal feedingstuffs. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH Threshold Limit Values (TLV)

Components	Type	Value
butane (CAS 106-97-8)	STEL	1000 ppm
cyclohexane (CAS 110-82-7)	TWA	100 ppm
heptane (CAS 142-82-5)	STEL	500 ppm
	TWA	400 ppm
hexane (CAS 110-54-3)	TWA	50 ppm

US. ACGIH Threshold Limit Values (TLV)

Components	Type	Value
Naphtha (Petroleum), Hydrotreated Light (CAS 64742-49-0)	TWA	100 ppm

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended

Components	Type	Value
butane (CAS 106-97-8)	TWA	1000 ppm
cyclohexane (CAS 110-82-7)	TWA	344 mg/m3 100 ppm
heptane (CAS 142-82-5)	STEL	2050 mg/m3 500 ppm
	TWA	1640 mg/m3 400 ppm
hexane (CAS 110-54-3)	TWA	176 mg/m3 50 ppm

Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances Workers Compensation Board, as amended

Components	Type	Value
butane (CAS 106-97-8)	STEL	1000 ppm
cyclohexane (CAS 110-82-7)	TWA	100 ppm
hexane (CAS 110-54-3)	TWA	20 ppm

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended

Components	Type	Value
butane (CAS 106-97-8)	STEL	1000 ppm
cyclohexane (CAS 110-82-7)	TWA	100 ppm
heptane (CAS 142-82-5)	STEL	500 ppm
	TWA	400 ppm
hexane (CAS 110-54-3)	TWA	50 ppm
Naphtha (Petroleum), Hydrotreated Light (CAS 64742-49-0)	TWA	100 ppm

Canada. New Brunswick OELs: Threshold Limit Values (TLVs) Based on the 1991 and 1997 ACGIH TLVs and BEIs Publication (New Brunswick Regulation 91-191)

Components	Type	Value
butane (CAS 106-97-8)	STEL	1000 ppm
cyclohexane (CAS 110-82-7)	TWA	100 ppm
heptane (CAS 142-82-5)	STEL	500 ppm
	TWA	400 ppm
hexane (CAS 110-54-3)	TWA	50 ppm

Canada. Ontario OELs (Regulation 833, Control of Exposure to Biological or Chemical Agents), as amended

Components	Type	Value
butane (CAS 106-97-8)	STEL	1000 ppm
cyclohexane (CAS 110-82-7)	TWA	100 ppm
heptane (CAS 142-82-5)	STEL	500 ppm
	TWA	400 ppm
hexane (CAS 110-54-3)	TWA	50 ppm

Canada. Quebec OELs (Regulation respecting occupational health and safety, v. S-2.1, r.13), as amended

Components	Type	Value
butane (CAS 106-97-8)	TWA	1900 mg/m3
		800 ppm
cyclohexane (CAS 110-82-7)	TWA	100 ppm
		500 ppm
heptane (CAS 142-82-5)	STEL	500 ppm
		400 ppm
hexane (CAS 110-54-3)	TWA	176 mg/m3
		50 ppm

Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996; Table 21), as amended

Components	Type	Value
cyclohexane (CAS 110-82-7)	15 minute	150 ppm
	8 hour	100 ppm
heptane (CAS 142-82-5)	15 minute	500 ppm
	8 hour	400 ppm
hexane (CAS 110-54-3)	15 minute	62.5 ppm
	8 hour	50 ppm

Biological limit values**ACGIH Biological Exposure Indices (BEI)**

Components	Value	Determinant	Specimen	Sampling Time
cyclohexane (CAS 110-82-7)	50 mg/g	1,2-Cyclohexanediol, with hydrolysis	Creatinine in urine	*
hexane (CAS 110-54-3)	0.5 mg/l	2,5-Hexanedione, without hydrolysis	Urine	*

* - For sampling details, please see the source document.

Exposure guidelines**Canada - Alberta OELs: Skin designation**

hexane (CAS 110-54-3) Can be absorbed through the skin.

Canada - British Columbia OELs: Skin designation

hexane (CAS 110-54-3) Can be absorbed through the skin.

Canada - Manitoba OELs: Skin designation

hexane (CAS 110-54-3) Danger of cutaneous absorption
Naphtha (Petroleum), Hydrotreated Light (CAS 64742-49-0) Danger of cutaneous absorption

Canada - Ontario OELs: Skin designation

hexane (CAS 110-54-3) Can be absorbed through the skin.

Canada - Quebec OELs: Skin designation

hexane (CAS 110-54-3) Can be absorbed through the skin.

Canada - Saskatchewan OELs: Can be absorbed through the skin.

hexane (CAS 110-54-3) Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

hexane (CAS 110-54-3) Danger of cutaneous absorption
Naphtha (Petroleum), Hydrotreated Light (CAS 64742-49-0) Danger of cutaneous absorption

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Ensure adequate ventilation, especially in confined areas. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

Eye/face protection Face-shield. Eye wash fountain is recommended.

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other	Wear chemical protective equipment that is specifically recommended by the manufacturer. Use of an impervious apron is recommended. It may provide little or no thermal protection.
Respiratory protection	If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	Observe any medical surveillance requirements. When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Physical state	Gas.
Form	Gaseous. Aerosol.
Color	Colorless
Odor	Solvent.
Melting point/freezing point	Not available.
Boiling point or initial boiling point and boiling range	Not available.
Flammability	Flammable gas. Not available.
Upper/lower flammability or explosive limits	
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Flash point	-156.0 °F (-104.4 °C) Propellant Estimated
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
pH	Not available.
Kinematic viscosity	Not available.
Solubility	
Solubility (water)	Not available.
Vapor pressure	Not available.
Density and/or relative density	
Density	0.55 g/cm ³ estimated
Relative density	0.608 g/cm ³ estimated
Vapor density	Not available.
Particle characteristics	Not available.
Other information	
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
Specific gravity	0.61 estimated

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Risk of explosion.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use. Hazardous polymerization does not occur.
Conditions to avoid	Heat, flames and sparks. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents. Chlorine. Fluorine. Nitrates. Do not mix with other chemicals.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause drowsiness or dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.
Skin contact	Causes skin irritation. May cause an allergic skin reaction. Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness or dizziness. Nausea, vomiting. May cause respiratory irritation. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways.

Components	Species	Test Results
------------	---------	--------------

cyclohexane (CAS 110-82-7)

Acute

Oral

LD50

Rabbit

> 5000 mg/kg

heptane (CAS 142-82-5)

Acute

Inhalation

LC50

Rat

103 mg/m³, 4 Hours

hexane (CAS 110-54-3)

Acute

Dermal

LD50

Rabbit

3000 mg/kg

Oral

LD50

Rat

28710 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye irritation Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer. Due to partial or complete lack of data the classification is not possible.

Skin sensitization May cause an allergic skin reaction. Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

ACGIH Carcinogens

Naphtha (Petroleum), Hydrotreated Light (CAS 64742-49-0) A3 Confirmed animal carcinogen with unknown relevance to humans.

Canada - Manitoba OELs: carcinogenicity

Naphtha (Petroleum), Hydrotreated Light (CAS 64742-49-0) Confirmed animal carcinogen with unknown relevance to humans.

Reproductive toxicity Mutagenic effects. May cause reproductive system disorder and/or damage. Suspected of damaging fertility or the unborn child.

Specific target organ toxicity - single exposure May cause respiratory irritation. May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard Not likely, due to the form of the product. May be fatal if swallowed and enters airways. Not an aspiration hazard.

Chronic effects Hazardous by OSHA criteria. Prolonged inhalation may be harmful. May cause damage to organs through prolonged or repeated exposure. Repeated absorption may cause disorder of central nervous system, liver, kidneys and blood. Prolonged exposure may cause chronic effects.

Further information Symptoms may be delayed.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components	Species	Test Results
cyclohexane (CAS 110-82-7)		
Aquatic		
<i>Acute</i>		
Fish	LC50	Striped bass (<i>Morone saxatilis</i>) 8.3 mg/l, 96 hours
heptane (CAS 142-82-5)		
Aquatic		
<i>Acute</i>		
Fish	LC50	Mozambique tilapia (<i>Tilapia mossambica</i>) 375 mg/l, 96 hours
hexane (CAS 110-54-3)		
Aquatic		
<i>Acute</i>		
Fish	LC50	Fathead minnow (<i>Pimephales promelas</i>) 2.101 - 2.981 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

butane	2.89
cyclohexane	3.44
heptane	4.66
hexane	3.9

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions). Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner.

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

14. Transport information

IATA

UN number	UN1950
UN proper shipping name	Aerosols, flammable, Limited Quantity
Transport hazard class(es)	
Class	2.1
Subsidiary hazard	-
Packing group	-
Environmental hazards	No

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IMDG

UN number UN1950
UN proper shipping name Aerosols, flammable, Limited Quantity

Transport hazard class(es)
Class 2.1

Subsidiary hazard -

Packing group -


Environmental hazards
Marine pollutant No.

EmS Not assigned.


Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

IATA



IMDG



General information IMDG Regulated Marine Pollutant.

15. Regulatory information

Canadian regulations

This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR. This product has been classified in accordance with the hazard criteria of the CPR and the SDS contains all the information required by the CPR.

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations

The product is classified and labelled in accordance with EC directives or respective national laws. Pregnant women should not work with the product, if there is the least risk of exposure. Young people under 18 years old are not allowed to work with this product according to EU Directive 94/33/EC on the protection of young people at work, as amended.

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information

Issue date 06-25-2018

Revision date 03-14-2025

Version # 08

Further information HMIS® is a registered trade and service mark of the NPCA.

References
 ACGIH
 EPA: AQUIRE database
 IARC Monographs. Overall Evaluation of Carcinogenicity
 NLM: Hazardous Substances Data Base

Disclaimer
 The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Malco Products, Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use.

Revision information This document has undergone significant changes and should be reviewed in its entirety.