

MALCO[®] TRU-POLISH[®] (1973)

DESCRIPTION

Tru-Polish[®] uses advanced abrasive technology to remove P3000 grit and finer sand scratches, car wash scratches and swirl marks left after compounding on most new and aged clear coat surfaces. This innovative polish produces a flawless, swirl-free finish with deep gloss without the use of waxes, fillers or silicones. This waterbased formula contains special lubricants for a longer work time and easy cleanup.

DIRECTIONS

Shake well before using. For best results in removing light scratches, use with a Malco Hornet Short-Cut pad (#800131) or Malco Green Polish pad (#810148). Apply a 1" (25mm) dab of Tru-Polish to a 2' x 2' (.6 m x .6 m) section and spread with the pad before initiating rotation. Buff at speeds between 1200 – 1800 rpm. Recommended buffing speed is 1400 rpm. Work the buffer slowly left to right and front to back, using light to medium surface pressure, slowly reducing pressure with subsequent passes. Do not buff to a dry surface. Tru-Polish is designed to stay wet throughout the entire polishing process to achieve an optimal finish. If buffing surface begins to dry, apply more product and continue to buff. Wipe surface with a clean microfiber cloth (#800135). For a flawless, swirl-free finish on dark cars, repeat polishing steps above with a seasoned Malco Blue Foam Pad (#810144) at speeds between 1000 - 1600 rpm. Recommended buffing speed is 1400 rpm.

FEATURES AND BENEFITS

Advances abrasive technology cuts P3000 sand scratches	Water-based formula contains special lubricants for long work time and easy cleanup
Removes compounding swirls and minor oxidation	Leaves a flawless, swirl-free finish
Produces deep gloss and glass-like finish	Contains no waxes, fillers or silicones

PACKAGE SIZES

- 32 fl. oz. (Part number: 197332)
- 1 gallon (Part number: 197301)