

EPIC® ASCEND CERAMIC COATING (109380)

DESCRIPTION

EPIC ASCEND Ceramic Coating is specially formulated to offer a superior high-gloss finish, abrasion resistance, and enhanced UV protection. This special formulation bonds with the clear coat to create a slick surface and a high level of hydrophobicity that prevents dirt, water spots, and other contaminants from adhering to paint. When professionally installed, EPIC ASCEND Ceramic Coating will provide your vehicle with the ultimate “wet” look and is backed by a 4 year/48,000-mile warranty.

DIRECTIONS

EPIC ASCEND Ceramic Coating requires a clean, smooth surface for proper adhesion. Wash, clay bar, and machine polish your vehicle prior to application. We recommend washing with MALCO® CW-37™ (Part #1057) and correcting paint imperfections with the EPIC Paint Correction System. If you cannot achieve a professional level of cleaning and paint correction on your own, please seek professional help. Ensure the vehicle is at room temperature (50°F - 75°F). Only apply the product in a covered, dust-free garage and allow the vehicle to remain inside for at least 24 hours afterward. For maximum results:

- Put on a pair of rubber gloves for protection. Shake product well prior to use.
- Clean and prep your surface with EPIC Ceramic Final Prep Wipe (Part #1097), using a lint-free cloth.
- Wrap a Suede Cloth around the Applicator Pad. For the first application, put 6 to 8 drops of the ceramic coating directly onto the cloth and immediately reseal the product. Put 4 – 6 drops on the cloth for subsequent applications.
- Apply the coating to the vehicle surface in a crosshatch pattern, using even pressure. We recommend working in a defined 20-in x 20-in area until the product is worked into the clear coat.
- Expect the coated area to rainbow or flash within 30-90 seconds of application. At this point, begin removing the product with a clean, microfiber towel. Be sure to remove any remaining residue.
- Repeat all steps to coat the entire vehicle, using an overlapping technique on each section to ensure full coverage.
- Keep the vehicle in a controlled environment for at least 12 hours while keeping it dry for a minimum of 24 hours. Complete bonding with the paint can take up to seven days, so it is vital to have garage access.

FEATURES & BENEFITS

Easy to Apply

Industry's easiest-to-apply coating system with enhanced working time

Bonds with Clear Coat

Provides an outstanding depth of gloss and slick surface

Protects Paint

Abrasion resistance, enhanced UV protection

Longevity

Helps protect the vehicle surface for 4 years/48K miles

Barrier Against Water

Outstanding hydrophobic, oleophobic, and slick properties

Repels Contamination

Allows dirt, water spots and contaminants to slide right off

PACKAGE SIZES

1 – 30 ml

Part number: 109380

PRODUCT FAQs

Q1: What should I use to apply Malco EPIC ASCEND Ceramic Coating?

A1: Use a MALCO sponge applicator with suede cloth or a microfiber ceramic coating applicator sponge for application. Applicators are designed for one use only and should be disposed of upon completion.

Q2: How long does it take to apply EPIC ASCEND Ceramic Coating?

A2: It depends on the amount of paint correction required beforehand and the experience level of the installer. You want to be sure you do not rush the application. A few hours are typical.

Q3: Is one layer of coating enough to provide protection?

A3: Yes, one layer is enough. Additional layers can be applied but do not necessarily increase protection.

Q4: How do I know when the coating is completely worked into the clearcoat?

A4: Continue wiping with the applicator in a cross hatch, until you no longer see any more 'wet' coating. You will notice rainbowing and feel a slight resistance as the coating is fully worked in.

Q5: What surfaces can this product be safely applied to?

A5: This product can be applied safely to painted surfaces, glass, and plastic trim.