



## VELOCITY™ ONE-STEP POLISH AND WAX (2650)

### DESCRIPTION

VELOCITY One-Step Polish and Wax is designed to remove light to medium paint defects while leaving behind a slick waxed surface with lasting protection for up to 90 days. This all-in-one compound will quickly and easily remove swirls, imperfections and up to P3000 sand scratches while leaving a deep glossy finish. Malco Velocity One-Step Polish and Wax offers a long working window and a dust-free application. This can be applied with an orbital, rotary or by hand with a variety of foam pads or microfiber applicators. Malco Velocity One-Step Polish and Wax features easy removal allowing a full vehicle application before wiping off.

### DIRECTIONS

Velocity can be used indoors, in a shaded area, and in direct sunlight. For best results clean and decontaminate paint surface with Malco CW-37 or similar car wash. For extremely damaged surfaces a Heavy-Duty compound such as Tru-Grit or EPIC may be required for initial correction. Shake VELOCITY ONE STEP POLISH AND WAX well. Apply 4 medium sized drops of compound to pad and work in a crosshatch pattern until the compound turns from yellow to opaque in a 2' x 2' section. To ensure maximum protection, allow the product to flash or dry on the surface before removing with a microfiber. Note: The entire car may be polished prior to removal. If using an orbital polisher, apply at a low-speed setting, then buff at setting 4-6, if using a rotary polisher, apply at slowest speed and then buff between 1,000 - 1,400 RPM. If working by hand use a clean, soft applicator for the best results.

### FEATURES & BENEFITS

#### One-Step Technology

Polishes and protects in one easy step

#### Easy to Use

Easy, wipe-off formula

#### Striking Finish

Produces a high gloss

#### Versatile Application

Can be applied with orbital and rotary buffers or by hand

#### Moderate Cutting

Removes up to P3000 sand scratches

#### VOC Compliant

Adheres to regulations regarding volatile organic compounds

#### Body Shop Safe

Safely to use in an environment where fresh paint is being sprayed

### PACKAGE SIZES

#### 6 – 16 oz.

Part number: 265016

#### 4 – 1 Gallon

Part number: 265001