Safety Data Sheet

Printing date 08/13/2024 Revised On 08/13/2024

1 Identification of the substance and manufacturer

Trade name: **GLOSS BLACK HT-1803**

Product code: ZB00980003
Recommended use: Paint and coatings application.
Uses advised against: Any that differs from the recommended use.
Manufacturer/Supplier: Hi-Tech Industries
33106 West 8 Mile Road
Farmington, MI 48336
phone: 248-358-5533
Emergency telephone number: INFOTRAC 1-800-535-5053 (North America), 1-352-323-3500 (International)

2 Hazard(s) identification

Classification of the substance or mixture

Flammable Aerosols 1	H222 Extremely flammable aerosol.
Gases under Pressure - Liquefied gas	H280 Contains gas under pressure; may explode if heated.
Eye Irritation 2A	H319 Causes serious eye irritation.
Toxic to Reproduction 1B	H360 May damage fertility or the unborn child.
Specific Target Organ Toxicity - Single Exposure 3	H336 May cause drowsiness or dizziness.
Specific Target Organ Toxicity - Repeated Exposure 2	H373 May cause damage to organs through prolonged or repeated exposure.

Additional information:
GHS Hazard pictograms



GHS02 GHS04 GHS07 GHS08

Signal word Danger
Hazard statements
Extremely flammable aerosol.
Contains gas under pressure; may explode if heated.
Causes serious eye irritation.
May damage fertility or the unborn child.
May cause drowsiness or dizziness.
May cause damage to organs through prolonged or repeated exposure.
Precautionary statements
Obtain special instructions before use.
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Do not spray on an open flame or other ignition source.
Pressurized container: Do not pierce or burn, even after use.
Do not breathe dust/fume/gas/mist/vapors/spray.
Wash thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Call a poison center/doctor if you feel unwell.
If eye irritation persists: Get medical advice/attention.
Store locked up.
Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Dispose of contents/container in accordance with local/regional/national/international regulations.
HMIS-ratings (0 - 4):
Health= 1
Fire= 4
Physical Hazard= 3
PPE----B

3 Composition/information on ingredients

Chemical characterization: Mixtures
Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:

67-64-1	Acetone	25-50%
74-98-6	propane	15-25%
106-97-8	n-butane	10-15%
64742-89-8	VM&P Naphtha	5-10%
64742-47-8	Mineral Spirits	5-10%
108-88-3	Toluene	1-5%
67-63-0	Isopropyl Alcohol	1-5%

4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.
After skin contact: Remove contaminated clothing. Wash exposed area with soap and water.
After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
After swallowing: Rinse out mouth and then drink plenty of water.
Rinse mouth with water. Do not induce vomiting.

(Contd. on page 2)

Safety Data Sheet

Trade name: GLOSS BLACK HT-1803

(Contd. of page 1)

Most important symptoms and effects: Dizziness
Indication of any immediate medical attention needed: No further relevant information available.

5 Fire-fighting measures

Extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray.
Special hazards: Can form explosive gas-air mixtures.
Protective equipment for firefighters: A respiratory protective device may be necessary.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures: Wear protective equipment. Keep unprotected persons away.
Use respiratory protective device against the effects of fumes/dust/aerosol.

Methods and material for containment and cleaning up: Dispose contaminated material as waste according to section 13.

7 Handling and storage

Precautions for safe handling Use only in well ventilated areas.
Storage requirements: Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.
Store locked up.

8 Exposure controls/personal protection

Components with limit values that require monitoring at the workplace:

67-64-1 Acetone	
PEL (USA)	Long-term value: 2400 mg/m³, 1000 ppm
REL (USA)	Long-term value: 590 mg/m³, 250 ppm
TLV (USA)	Short-term value: 500 ppm Long-term value: 250 ppm A4, BEI
74-98-6 propane	
PEL (USA)	Long-term value: 1800 mg/m³, 1000 ppm
REL (USA)	Long-term value: 1800 mg/m³, 1000 ppm
TLV (USA)	see Appendix F Minimal oxygen content (D, EX)
106-97-8 n-butane	
REL (USA)	Long-term value: 1900 mg/m³, 800 ppm
TLV (USA)	Short-term value: 1000 ppm (EX)
108-88-3 Toluene	
PEL (USA)	Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift
REL (USA)	Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm
TLV (USA)	Long-term value: 20 ppm BEI, OTO, A4
67-63-0 Isopropyl Alcohol	
PEL (USA)	Long-term value: 980 mg/m³, 400 ppm
REL (USA)	Short-term value: 1225 mg/m³, 500 ppm Long-term value: 980 mg/m³, 400 ppm
TLV (USA)	Short-term value: 400 ppm Long-term value: 200 ppm BEI, A4

Ingredients with biological limit values:

67-64-1 Acetone	
BEI (USA)	25 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)

(Contd. on page 3)

Safety Data Sheet

Trade name: GLOSS BLACK HT-1803

(Contd. of page 2)

108-88-3 Toluene	
BEI (USA)	0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene 0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene 0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)
67-63-0 Isopropyl Alcohol	
BEI (USA)	40 mg/L Medium: urine Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific)

Hygienic protection: Keep away from foodstuffs and animal feed. Wash hands after use.
Immediately remove all soiled and contaminated clothing.
Wash hands after use.
Store protective clothing separately.
Avoid contact with the eyes and skin.
Do not eat or drink while working.

Breathing equipment: A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a NIOSH approved respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

Hand protection: Nitrile gloves.
The glove material must be impermeable and resistant to the substance.

Eye protection: Tightly sealed goggles

9 Physical and chemical properties

Appearance: Aerosol.
Odor: Aromatic
Odor threshold: Not determined.

pH-value: Not determined.
Melting point/Melting range Undetermined.
Boiling point: -110 °C (-166 °F)

Flash point: -19 °C (-2.2 °F)
Flammability (solid, gas): Extremely flammable.

Decomposition temperature: Not determined.

Auto igniting: Product is not self-igniting.

Danger of explosion: In use, may form flammable/explosive vapour-air mixture.
Lower Explosion Limit: 1.7 Vol %
Upper Explosion Limit: 10.9 Vol %

Vapor pressure: Not determined.
Relative Density: Between 0.77 and 0.85 (Water equals 1.00)
Vapor density Not determined.
Evaporation rate Not applicable.
Partition coefficient: n-octonal/water: Not determined.

Solubility: Not determined.
Viscosity: Not determined.

10 Stability and reactivity

Reactivity: Stable at normal temperatures.
Conditions to avoid: Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures.
Chemical stability: Not fully evaluated.
Possibility of hazardous reactions: No dangerous reactions known.
Incompatible materials: No further relevant information available.
Hazardous decomposition: No dangerous decomposition products known.

(Contd. on page 4)

Safety Data Sheet

(Contd. of page 3)

11 Toxicological information

LD/LC50 values that are relevant for classification:

67-63-0 Isopropyl Alcohol

Oral	LD50	4,570 mg/kg (rat)
Dermal	LD50	13,400 mg/kg (rab)
Inhalative	LC50/4 h	30 mg/l (rat)

Information on toxicological effects: No data available.
Skin effects: No irritant effect.
Eye effects: Irritating effect.
Sensitization: No sensitizing effects known.

12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.
Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.
Other information: This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), per and polyfluoroalkyl substances (PFA's), or chlorinated solvents.
Bioaccumulative potential: No further relevant information available.
Mobility in soil: No further relevant information available.
Other adverse effects: No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.
Recommendation: Completely empty cans should be recycled.
Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

UN-Number UN1950
DOT UN1950
DOT DOT
Aerosols, flammable
ADR 1950 Aerosols
Transport hazard class(es):
Class 2.1 Gases
Marine pollutant: No
Special precautions for user: Warning: Gases
EMS Number: F-D,S-U
Packaging Group: --
UN "Model Regulation": UN1950, Aerosols, 2.1

15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

108-88-3	Toluene
67-63-0	Isopropyl Alcohol

Toxic Substances Control Act (TSCA): All hazardous ingredients are found on the inventory list of substances.
Canadian Domestic Substances List (DSL): All ingredients are listed or exempted.
Consumer Product Safety Comission (CPSC): This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

1333-86-4	Carbon black
100-41-4	ethyl benzene

Prop 65 chemicals known to cause birth defects or reproductive harm:

108-88-3	Toluene

EPA:

67-64-1	Acetone	I

16 Other information

Contact: Regulatory Affairs